


## DAMPING SOUND INSULATING PANEL

**Patent number:** JP10266388  
**Publication date:** 1998-10-06  
**Inventor:** YAOI KENICHI; OKUDAIRA YUZO; ONISHI KENJI; KOBAYASHI SUSUMU; HORIE FUJIO  
**Applicant:** MATSUSHITA ELECTRIC WORKS LTD;; KINKI SHARYO CO LTD  
**Classification:**  
- **international:** E04B1/86; E04C2/36  
- **europaean:**  
**Application number:** JP19970076056 19970327  
**Priority number(s):**


**Also published as:**

 JP10266388 (A)

### Abstract of JP10266388

**PROBLEM TO BE SOLVED:** To form a damping sound insulating panel having high damping sound insulating property with lightweight by fluidally sealing inorganic powder in a hollow panel inside space, and converting vibration energy of powder particles into thermal energy.

**SOLUTION:** A partition plate 11 composed of aluminum honeycomb material exists between aluminum surface materials 10, 10 to form a hollow panel, and powder 2 is fluidally sealed in the hollow part to form a damping sound insulating panel. The powder 2 preferably has an inside space or minute holes, made an inorganic system such as glass beads, a silica balloon, vermiculite and perlite, an acrylic sphere can be also used, a particle diameter is made 30-1000  $\mu\text{m}$ , exciting acceleration is in the neighborhood of 1G, and a fluidal phenomenon produced in the powder 2 is effectively utilized to convert vibration energy of the particles of the powder 2 into thermal energy. Thus, when the damping sound insulating panel is used for floor material, wall material and ceiling material of a shinkansen vehicle, a noise level can be reduced in a wide frequency band.



**BEST AVAILABLE COPY**

---

Data supplied from the **esp@cenet** database - Patent Abstracts of Japan